## KombiSIGN 71 / LED EVS Element 644 LED EVS element 24VDC CL



ļ

644.440.55	
KombiSIGN 71	
CAL DATA	
	66 mm
	70 mm
	PC
ır	Clear
category	IP65
mperature minimum	-20°C
mperature maximum	+50°C
n packaging	83 g
ight	68 g
AL DATA	
/oltage	24V
voltage type	DC
	+/- 10%
ational voltage	24 VDC
ational current	250 mA
sh current	500 mA
class	Protection class 2
egree	3
ΔΤΑ	
e	LED
r	White
nal image	EVS
optical	50,000 h maximum
L DATA	
vith CE	Yes
vith RoHS directive	Yes
	Yes
vith ATEX-directive	No
vith CCC	No
vith UL	cULus
ting	Type 12
vith FCC	No
vith IC	No
ate available	Yes
vith UKCA (Importer)	Yes (WERMA (UK) Ltd.)
· · · · · · ·	· · · · · · ·
	KombiSIGN 71 CAL DATA CAL DATA CAL DATA Category mperature minimum mperature maximum


For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

ļ

## KombiSIGN 71 / LED EVS Element 644 LED EVS element 24VDC CL

Conforms with AS-I	No
ICAO Certification	No
Conforms with DNV	No
Conforms with RoHS CN	No
Conforms with VdS	No
MTTF-value [years]	1348

## DRAWING



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.