

KombiSIGN 71 / WIN

# WIN transmitter KombiSIGN 71 24VAC/DC BK



Part No.: 860.640.05



## MECHANICAL DATA

|                             |       |
|-----------------------------|-------|
| Height                      | 66 mm |
| Diameter                    | 70 mm |
| Materials                   | PC    |
| Housing colour              | Black |
| Protection category         | IP65  |
| Connection                  | USB   |
| Working temperature minimum | -20°C |
| Working temperature maximum | +50°C |
| Weight with packaging       | 96 g  |
| Product weight              | 77 g  |

## ELECTRICAL DATA

|                             |                    |
|-----------------------------|--------------------|
| Operating voltage           | 24V                |
| Operating voltage type      | AC/DC              |
| Operating voltage frequency | 50Hz               |
| Operating voltage tolerance | +/- 10%            |
| Rated operational voltage   | 24 VDC             |
| Rated operational current   | 40 mA              |
| Rated inrush current        | 430 mA             |
| Protection class            | Protection class 2 |
| Pollution degree            | 2                  |
| connectivity                | WIN                |

## OPTICAL DATA

|                      |                  |
|----------------------|------------------|
| Service life optical | 50,000 h maximum |
|----------------------|------------------|

## APPROVAL DATA

|                              |                                |
|------------------------------|--------------------------------|
| Conforms with CE             | No                             |
| Conforms with RoHS directive | Fulfills substance restriction |
| WEEE                         | Yes                            |
| Conforms with ATEX-directive | No                             |
| Conforms with CCC            | No                             |
| Conforms with UL             | cULus                          |
| UL Type Rating               | Type 12                        |
| Conforms with FCC            | Yes                            |
| Conforms with IC             | Yes                            |
| EAC certificate available    | Yes                            |
| Conforms with AS-I           | No                             |
| ICAO Certification           | No                             |




For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.

KombiSIGN 71 / WIN

## WIN transmitter KombiSIGN 71 24VAC/DC BK

|                       |    |
|-----------------------|----|
| Conforms with DNV     | No |
| Conforms with RoHS CN | No |
| Conforms with VdS     | No |

### DRAWING



For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.